

Ausführung construction	Steckmuffen (SM + SMVA) Endmuffen (EM + EMX) couplings (SM + SMVA) end sleeve (EM + EMX)
Werkstoff material	verzinkt / feuerverzinkt Edelstahl galvanised steel / hot dip galv. stainless steel
Temperatur temperature	-60°C - +250°C -60°C - +600°C (V2A + V4A)
Schutzart protection	
gemäß according to	IEC EN 61386

SM feuerverzinkt

Art. Nr. art. no.	Länge length	NW DN	AD mm OD mm	VPE unit
SM16	-	M16	16	25
SM20	-	M20	20	25
SM25	-	M25	25	10
SM32	-	M32	32	10
SM40	-	M40	40	5
SM50	-	M50	50	5
SM63	-	-	60	1

EM feuerverzinkt

Art. Nr. art. no.	Länge length	NW DN	AD mm OD mm	VPE unit
EM16	-	M16	16	25
EM20	-	M20	20	25
EM25	-	M25	25	10
EM32	-	M32	32	10
EM40	-	M40	40	5
EM50	-	M50	50	5
EM63	-	-	60	1

SM V2A

Art. Nr. art. no.	Länge length	NW DN	AD mm OD mm	VPE unit
SMVA16	-	M16	16	25
SMVA20	-	M20	20	25
SMVA25	-	M25	25	10
SMVA32	-	M32	32	10
SMVA40	-	M40	40	5
SMVA50	-	M50	50	5
SMVA63	-	M63	63	1

EM V4A

Art. Nr. art. no.	Länge length	NW DN	AD mm OD mm	VPE unit
EMX16	-	M16	16	25
EMX20	-	M20	20	25
EMX25	-	M25	25	10
EMX32	-	M32	32	10
EMX40	-	M40	40	5
EMX50	-	M50	50	5
EMX63	-	-	60	1

Eigenschaften
Steckmuffen für die Elektroinstallation gemäß
IEC EN 61836.

Properties
Couplings for electro-installation according to
IEC EN 61836.

